



CLEAR VIEW® CAP KIT

Instructions for MT Dual Port Series

- Remove OEM cap retaining the washers, discard old bolts.
- Allow oil to completely drain.
- Remove any old gasket material from face of roller and idler hubs.
- Using the enclosed replacement bolts & your OEM washers, place the Kile® Clear View® caps, with gaskets, to the hub.
- Tighten bolts to 35-40 inch pounds.
- Replace oil to manufacture specifications.
- Tighten plugs with plug wrench.

Use only soap and water to clean caps, no solvents (solvents can cause clouding and premature failure of caps. Solvent use will void warranty)

Do not over tighten bolts

Part ID	Description	MT 700/2 Quantities	MT 800/2 Quantities
K MT6511R	Roller Cap	12	16
K MT6515I	Idler Cap	4	4
K6512RGE	Roller Gasket	12	16
K 6514IGE	Idler Gasket	4	4
K 1215P & K012	Plug with oring	32	40
8mmx20 bolt	MT cap bolt	92	112
K 1216 W	Plug wrench	1	1

Kile® Clear View® Caps are covered by one or more of the following US Patent numbers: D666,227; #D689,108; #D699,772; #D700,227; #8,684,474; #8,833,872; #8,979,215; #9,120,514; #9,399,369; #9,458,965

